



Vent-Free Fireplace Systems



ProCom Select provides a complete line of Vent-Free Fireplace Systems to address your heating needs and to enhance your décor. The firebox systems offer options from thermostat operation to remote control and features Patented Dual Fuel Technology to increase the ease of installation. ProCom Select mantels are designed to complement your household furnishings by featuring furniture grade finishes along with superior construction. *ProCom Select: Fireplace Systems Providing Affordable Luxury.*

Vent-Free Fireplace Systems



FBD32RT + M32-JHC



FBD400RT-J-LM

Fireplace Dimensions - 28" Jefferson Series

	Height	Width	Depth	Weight
FBD28T-J-MM/ HC	41.60"	43.20"	17.00"	132 lbs.
FBD28RT-J-MM/HC	41.70"	43.30"	16.70"	132 lbs.
FBD28RTC-J-HC	41.60"	51.00"	29.90"	112 lbs.

Product Specific Features

- Mantel and base fully assembled in 1 box with 28" insert
- Contains 5 hand painted, natural looking ceramic fiber logs
- T-Stat or On/ Off remote control
- Available in corner mantel with Heritage Cherry finish

Fireplace Dimensions - 32" Jefferson Series

	Height	Width	Depth	Weight
FBD32RT	33.27"	36.38"	18.38"	88.2 lbs.
M32-JMM/ HC	49.80"	50.75"	21"	119 lbs.

Product Specific Features

- Mantel and insert sold separately
- Contains 9 hand painted, natural looking ceramic fiber logs
- Thermostat remote control

Fireplace Dimensions - 400 Jefferson Series

	Height	Width	Depth	Weight
FBD400RT-J-LM/HC	44"	44"	18.19"	149 lbs.

Product Specific Features

- Unassembled mantel in KD packaging for cost savings
- Contains 6 hand painted, natural looking ceramic fiber logs
- Arched style working doors
- Thermostat remote control

Common Features

- Patented DUAL FUEL TECHNOLOGY
- All mantels feature a 7 step furniture grade finish
- Unique airflow technology built into the firebox for greater heat flow
- Dual yellow flame burner
- Zero clearance firebox for custom built-in application (28" and 32" only)
- Built-in O.D.S. (Oxygen Depletion System) for maximum safety
- Enjoy continuous heat even during a power failure, operates without electricity
- Logs are pinned for easy set up

Accessories

- 28 and 32 Series Blower: FIB100
- 400 Series Blower: QEB100

Warranty

3 year limited warranty

ANSI Z21.11.2 and PFS approved



Dual Fuel Technology provides with one appliance with 2 fuel options

BTU Rating Information

Fireplace Inserts	High	Low	Heat Range
FBD28T/ RT	26,000	15,000	800 Sq Ft.
FBD32RT	32,000	32,000	1,100 Sq. Ft.
FBD400RT	32,000	32,000	1,100 Sq. Ft.